TURBO JET NYLON



stone concrete | solid brick

CE CERTIFIED FOR APPLICATIONS ON CONCRETE/STONE AND SOLID MASONRY

TURBO JET Nylon Anchor
with **countersunk collar**
countersunk flat head nail screw white zinc plated

PREASSEMBLED



EAD 330196-01-0604
base material: a,b
Ø5, Ø6, Ø8

on line
G&B CALCULATION PROGRAM 4.3
professional design of anchorage in concrete

ART.	Ø x L t	DESCR.	SCREW	t fix	BOX	CARTON
	mm		mm	mm	pcs	pcs
93025	5x27	TJ5-27SV	3,5x32	5	100	3200
93026	5x37	TJ5-37SV	3,5x42	15	100	3200
93027	5x47	TJ5-47SV	3,5x52	25	100	1600
93028	6x32	TJ6-32SV	3,8x37	5	100	1600
93029	6x40	TJ6-40SV	3,8x45	10	100	1600
93030	6x55	TJ6-55SV	3,8x60	25	100	1600
93031	6x67	TJ6-67SV	3,8x72	37	100	800
93032	6x80	TJ6-80SV	3,8x85	50	50	800
93033	8x45	TJ8-45SV	4,8x50	10	100	800
93034	8x60	TJ8-60SV	4,8x65	25	100	800
93035	8x75	TJ8-75SV	4,8x80	40	100	800
93036	8x100	TJ8-100SV	4,8x105	65	50	400
93037	8x120	TJ8-120SV	4,8x125	85	50	400
93038	8x135	TJ8-135SV	4,8x140	100	50	400

TURBO JET NYLON Anchor
in a transparent plastic bucket
EASYBOX reusable

ART.	Ø x L t	DESCR.	SCREW	t fix	BOX	CARTON
	mm		mm	mm	pcs	pcs
93260	5x27	TJ5-27SV	3,5X32	5	800	4
93261	6x40	TJ6-40SV	3,8X45	10	400	4

Min.1 CARTON = 6 box

TURBO JET Nylon Anchor
with **countersunk collar**
countersunk flat head nail screw
STAINLESS STEEL AISI 304 (A2)

INOX (A2)

PREASSEMBLED



EAD 330196-01-0604
base material: a,b
Ø5, Ø6, Ø8

on line
G&B CALCULATION PROGRAM 4.3
professional design of anchorage in concrete

ART.	Ø x L t	DESCR.	SCREW	t fix	BOX	CARTON
	mm		mm	mm	pcs	pcs
HTTSI21	5x27	TJ5-27SVI	3,5x32	5	100	800
HTTSI22	5x50	TJ5-50SVI	3,5x55	25	100	1600
HTTSI23	6x40	TJ6-40SVI	3,8x45	10	100	1600
HTTSI24	6x55	TJ6-55SVI	3,8x60	25	100	1600
HTTSI30	6x80	TJ6-80SVI	3,8x85	50	50	800
HTTSI25	8x60	TJ8-60SVI	4,8x65	20	100	800
HTTSI26	8x75	TJ8-80SVI	4,8x80	40	100	800
HTTSI27	8x100	TJ8-100SVI	4,8x105	60	50	400
HTTSI28	8x120	TJ8-120SVI	4,8x125	80	50	400

TURBO JET Nylon Anchor
with **flat collar** grey RAL 7035
countersunk flat head nail screw white zinc plated

PREASSEMBLED



EAD 330196-01-0604
base material: a,b
Ø5, Ø6, Ø8

on line
G&B CALCULATION PROGRAM 4.3
professional design of anchorage in concrete

ART.	Ø x L t	DESCR.	SCREW	t fix	BOX	CARTON
	mm		mm	mm	pcs	pcs
93011	5x27	TJ5-27V	3,5x32	5	100	3200
93012	5x37	TJ5-37V	3,5x42	15	100	3200
93013	5x47	TJ5-47V	3,5x52	25	100	1600
93014	6x32	TJ6-32V	3,8x37	5	100	1600
93015	6x40	TJ6-40V	3,8x45	10	100	1600
93016	6x55	TJ6-55V	3,8x60	25	100	1600
93017	6x67	TJ6-67V	3,8x72	37	100	800
93018	6x80	TJ6-80V	3,8x85	50	50	800
93019	8x45	TJ8-45V	4,8x50	10	100	800
93020	8x60	TJ8-60V	4,8x65	25	100	800
93021	8x75	TJ8-75V	4,8x80	40	100	800
93022	8x100	TJ8-100V	4,8x105	65	50	400
93023	8x120	TJ8-120V	4,8x125	85	50	400
93024	8x135	TJ8-135V	4,8x140	100	50	400

TURBO JET Nylon Anchor
with **flat collar**
countersunk flat head nail screw
white zinc plated
bulked packed in Industrial Polybag

ART.	Ø x L t	DESCR.	SCREW	t fix	POLYBAG	CARTON
	mm		mm	mm	pcs	pcs
93527	5x27	TJ5-27V	3,5x32	5	800	4800
93632	6x32	TJ6-32V	3,8x37	5	600	3600
93640	6x40	TJ6-40V	3,8x45	10	500	3000