MA MULTIANCHOR POLYESTER RESIN

stone concrete | solid brick | semisolid brick | hollow brick | hollow concrete block

CE certified OPTION 7
for threaded bar applications on non-cracked concrete

G&B FISSAGGI PLANT 4
MA Multi Anchor
DoP : DPGEB1026

ETAG 001-5
OPTION 7
16 - 1020
ETA 16/0598
M8 - M24
European Technical Assessment

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ (A+ A B C)

CC40 410ml | **CC30** 300ml | **CC17** 175ml | **M17**

on line G&B CALCULATION PROGRAM 4.3 professional design of anchorage in concrete

(300ml)

Size **410-300ml**
Also available in a beige colour by request

ART.	DESCR.	CONTENT	MIXER	DURATION	CARTON	FOR GUN
		ml		months	pcs	
CC40	MA400	410	1 M17	18	12	PK1-PK11-PK15-PK16
CC30	MA300	300	1 M17	12	12	SK2-PK17
CC17	MA175	175	1 M17	12	12	SK2
CC40P	MA400 ●	410	1 M17	18	12	PK1-PK11-PK15-PK16
CC30P	MA300 ●	300	1 M17	12	12	SK2-PK17

SH-PRO SUPER HYBRID FORMULA HYBRID

STYRENE FREE HYBRID FORMULATION

Styrene free, without additives and solvents dangerous for environments and user

CE certified OPTION 7
for non-cracked concrete and solid and hollow brick masonry

WOOD-WOOD approved
for the installation of windows and doors

stone concrete | solid brick | semisolid brick | hollow brick | hollow concrete block | areated concrete

G&B FISSAGGI PLANT 4
Super Hybrid SH-PRO
DoP : DPGEB1020

EAD 330499-00-0601
OPTION 7
18 - 1020
ETA 18/0179
M8 - M24
European Technical Assessment

EAD 330076-00-0604
Use Category b,c,w/d
18 - 1020
ETA 18/0178
M8 - M12
European Technical Assessment

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ (A+ A B C)

LEED According to LEED IEQ 4.1

LEGNOLEGNO POSA QUALIFICATA SERRAMENTI LEGNO-ALLUMINIO-PVC [PO/SI-01]
Rapporto n. 007QI/12

ECOLOGICA



CC01 410ml | **CC02** 300ml | **M17** | **KITSH3** 300ml

on line G&B CALCULATION PROGRAM 4.3 professional design of anchorage in concrete

(300ml)

Size **410-300ml**
Also available in a beige colour by request

ART.	DESCR.	CONTENT	MIXER	DURATION	CARTON	FOR GUN
		ml		months	pcs	
CC01	SHPRO410	410	1 M17	18	12	PK1-PK11-PK15-PK16
CC02	SHPRO300	300	1 M17	12	12	SK2-PK17
CC01P	SHPRO410 ●	410	1 M17	18	12	PK1-PK11-PK15-PK16
CC02P	SHPRO300 ●	300	1 M17	12	12	SK2-PK17
KITSH3	SHPRO300	300	-	12	12	SK2-PK17

EXTREME HYBRID XTR
HYBRID VINYLESTER
STYRENE FREE

CE OPTION **1**

3 CE Certifications
- OPTION 1 for application on cracked and non-cracked concrete with THREADED BARS and REBARS

FIXATIONS IN SEISMIC ZONE C1 (M8 to M16) e C2 (M12 to M16)
for applications in dry, wet and flooded bore holes.

on line
G&B CALCULATION PROGRAM 4.3
professional design of anchorage in concrete

European Technical Assessment
EAD 330499-01-0601
OPTION 1
22 2873
ETA 22/0214
M8-M24/Ø8-Ø25
SEISMIC Cat. C1
M8-M16
SEISMIC Cat. C2
M12-M16

FIXING IN SEISMIC AREA
Seismic Cat. C1
M8-M16
Seismic Cat. C2
M12-M16

European Technical Assessment
EAD 330076-01-0604
Use Category b, c, d, d/d, w/w
22 2873
ETA 22/0211
M8-M16

European Technical Assessment
EAD 330087-01-0601
22 2873
ETA 22/0213
Ø8-Ø25

ÉMISSIONS DANS L'AIR INTÉRIEUR
A+ (A+ A B C)

LEED
According to LEED IEQ 4.1



CC37
410ml

CC38
300ml

M17

ART.	DESCR.	CONTENT	MIXER	DURATION	CARTON	FOR GUN
		ml		months	pcs	
CC37	XTR410	410	1 M17	18	12	PK1-PK11-PK30-PK16
CC38	XTR300	300	1 M17	12	12	SK2 - PK17

GEBOFIX PRO SISMIK VE-SF
VINYLESTER RESIN
STYRENE FREE

CE OPTION **1**

ULTRA CERTIFIED

HIGH PERFORMANCE FOR CRACKED CONCRETE AND APPLICATIONS IN SEISMIC ZONE

3 CE Certifications
- OPTION 1 cracked concrete
- for SOLID and HOLLOW MASONRY
- for POST-INSTALLED RE-BARS

FIXATIONS IN SEISMIC ZONE C1 (da M10 a M24) e C2 (da M12 a M20)
Can be used in dry, wet and flooded holes
FIRE RESISTANCE R120

on line
G&B CALCULATION PROGRAM 4.3
professional design of anchorage in concrete

European Technical Assessment
EAD 330499-01-0601
OPTION 1
13 1020
ETA 19/0699
M8-M30/Ø8-Ø32
SEISMIC Cat. C1
M10-M24
SEISMIC Cat. C2
M12-M20

FIXING IN SEISMIC AREA
Seismic Cat. C1
M10-M24
Seismic Cat. C2
M12-M20

European Technical Assessment
EAD 330076-00-0604
Use Category b,c,w/d
13 1020
ETA 16/0919
M8-M12

Feuerwider-standsklasse
R 120

European Technical Assessment
ETAG 001-5 TR23
10 1020
ETA 16/0599
Ø8-Ø32

ÉMISSIONS DANS L'AIR INTÉRIEUR
A+ (A+ A B C)

LEED
According to LEED IEQ 4.1



POUR UTILISATION EN CONTACT AVEC EAU POTABLE

(300ml)

CC13
410ml

CC14
345ml

CC32
300ml

M17

ART.	DESCR.	CONTENT	MIXER	DURATION	CARTON	FOR GUN
		ml		months	pcs	
CC13	PRO T400VE-SF	410	2 M17	18	12	PK1-PK11-PK30-PK16
CC14	PRO T345VE-SF	350	2 M17	18	12	PK5
CC32	PRO T300VE-SF	300	1 M17	12	12	SK2-PK17

GEBOFIX PRO SISMIK NORDIC VE-SF

CE OPTION 1

RESIN VINYLESTER WITHOUT STYRENE

stone concrete | CLS cracked | solid brick | semisolid brick | hollow brick | hollow concrete block

WINTER FORMULATION
APPLICATIONS AT LOW TEMPERATURES UP TO -20° C.

CE Certified OPTION 1
for application on cracked and non-cracked concrete with threaded bars and rebars



European Technical Assessment
EAD 330499-01-0601
OPTION 1
13 1020
ETA 19/0699
M8-M30/Ø8-Ø32
SEISMIC Cat. C1
M10-M24
SEISMIC Cat. C2
M12-M20

FIXING IN SEISMIC AREA
Seismic Cat. C1 M10-M24
Seismic Cat. C2 M12-M20

ÉMISSIONS DANS L'AIR INTÉRIEUR A+

LEED® According to LEED® IEQ 4.1

CCWT13 410ml | CCWT32 300ml | M17

on line G&B CALCULATION PROGRAM 4.3 professional design of anchorage in concrete

-20°C

ART.	DESCR.	CONTENT	MIXER	DURATION	CARTON	FOR GUN
		ml		months	pcs	
CCWT13	T410V NORDIC	410	1 M17	18	12	PK1-PK11-PK15-PK16
CCWT32	T300V NORDIC	300	1 M17	12	12	SK2-PK17



GEBOFIX EPO PLUS RE PURE EPOXY 3: 1 CERTIFIED CE OPTION 1

CE OPTION 1

a mixture to the ratio of 3:1

CE Approved OPTION 1
for cracked and non cracked concrete for threaded bar and rebar

CE Approved for fixing in SEISMIC AREA

stone concrete | CLS cracked | wood

G&B FISSAGGI PLANT 4
Gebofix EPO PLUS RE
DoP : DPGEB1009

European Technical Assessment
EAD 330499-00-0601
13 1020
ETA 17/0347
M8-M30/Ø8-Ø32
OPTION 1
SEISMIC Cat. C2
M12-M20

European Technical Assessment
ETAG 001-5 TR23
17 1020
ETA 17/0368
Ø8-Ø40

FIXING IN SEISMIC AREA
Seismic Cat. C2 M12-M20

ÉMISSIONS DANS L'AIR INTÉRIEUR A+

LEED® According to LEED® IEQ 4.1

CCPE585 585ml | CCPE385 385ml | CME12

on line G&B CALCULATION PROGRAM 4.3 professional design of anchorage in concrete

ART.	DESCR.	CONTENT	MIXER	DURATION	CARTON	FOR GUN
		ml		months	pcs	
CCPE585	EPO PLUS RE T585	585	1 CME12	24	12	CP19
CCPE385	EPO PLUS RE T385	385	1 CME12	24	12	CP18-CP19